



Specialty Paints & Products for  
Sign · Branding · Re-Imaging  
1.800.421.7961

---

## Q-PRIM™ FP1006™ GRAY FOAM PRIMER / SURFACER

---

**Q-PRIM™ FP1006™ FOAM Primer / Surfacers** is specifically designed for application as a primer / surfacer on HDU – High Density Urethane Foams and many other foam substrates used in the sign, exhibit and display industries to maximize ease of application, filling and sanding properties.

**Q-PRIM™ FP1006™** Foam Primer / Surfacers is a single component, fast, air-dry product that exhibits excellent filling and sanding characteristics.

QH&F **Environmentally Friendly** Product.

---

### APPLICATION:



**Safety:**

Use only NIOSH approved respirators and personal protection equipment recommended for the product used.

*Always review the MSDS – Material Safety Data Sheets before use.*




HDU type Foam boards used in the sign, exhibit and display industries.



**Surface Cleaning:**

Blow off surfaces with high-pressure clean air. HDU – High Density Foam type materials are very porous and liquid cleaning is not recommended.



**Application:**

Can be brushed, pad applied or sprayed: Apply 1-3 coats or as needed using a high quality china bristle brush or pad applicator. For spray application **Q-SOLV™ DR1270™ Sensitive Display Reducer** may be added. For large areas use **Q-SOLV™ DR1280™ Display Retarder** sparingly in addition to **Q-SOLV™ DR1270™ Sensitive Display Reducer**. Application by roller cover will result in a sacrifice in appearance.



**Dry Time To Topcoat:**

Dry to touch, handle and topcoat /recoat times vary, and are dependent on ambient temperature, % relative humidity and air movement which all play a significant role in dry times. Typical dry time is 30-45 minutes.

Always test surface preparation, primer and topcoat compatibility to determine acceptability before any production run.

**Disclaimer:** Technical information and suggested uses are believed to be reliable by QH&F Ltd., but such information or suggestions do not constitute a warranty. QH&F Ltd. has no control over the conditions under which the product is stored, handled, used or applied. Buyers must determine for themselves the suitability of each product for their specific use.